

[\[Team LiB \]](#)

- [Table of Contents](#)
- [Index](#)
- [Reviews](#)
- [Reader Reviews](#)
- [Errata](#)
- [Academic](#)

sendmail Cookbook

By [Craig Hunt](#)

Publisher: O'Reilly
Pub Date: December 2003
ISBN: 0-596-00471-0
Pages: 408

[Copyright](#)

[Dedication](#)

[Preface](#)

[Introduction](#)

[Using This Cookbook](#)

[Audience](#)

[Organization](#)

[Software Versions](#)

[Conventions](#)

[We'd Like to Hear from You](#)

[Acknowledgments](#)

[Chapter 1. Getting Started](#)

[Introduction](#)

[Recipe 1.1. Downloading the Latest Release](#)

[Recipe 1.2. Installing sendmail](#)

[Recipe 1.3. Compiling sendmail to Use LDAP](#)

[Recipe 1.4. Adding the regex Map Type to sendmail](#)

[Recipe 1.5. Compiling sendmail with SASL Support](#)

[Recipe 1.6. Compiling sendmail with STARTTLS Support](#)

[Recipe 1.7. Compiling in STARTTLS File Paths](#)

[Recipe 1.8. Building a sendmail Configuration](#)

[Recipe 1.9. Testing a New Configuration](#)

[Recipe 1.10. Logging sendmail](#)

[Chapter 2. Delivery and Forwarding](#)

[Introduction](#)

[Recipe 2.1. Accepting Mail for Other Hosts](#)

[Recipe 2.2. Fixing the Alias0 Missing Map Error and Creating Simple Aliases](#)

[Recipe 2.3. Reading Aliases via LDAP](#)
[Recipe 2.4. Configuring Red Hat 7.3 to Read Aliases from a NIS Server](#)
[Recipe 2.5. Configuring Solaris 8 to Read Aliases from a NIS Server](#)
[Recipe 2.6. Forwarding to an External Address](#)
[Recipe 2.7. Creating Mailing Lists](#)
[Recipe 2.8. Migrating Ex-Users to New Addresses](#)
[Recipe 2.9. Delivering Mail to a Program](#)
[Recipe 2.10. Using Program Names in Mailing Lists](#)
[Recipe 2.11. Allowing Nonlogin Users to Forward to Programs](#)
[Recipe 2.12. Fixing a .forward Loop](#)
[Recipe 2.13. Enabling the User Database](#)

[Chapter 3. Relaying](#)

[Introduction](#)

[Recipe 3.1. Passing All Mail to a Relay](#)
[Recipe 3.2. Passing Outbound Mail to a Relay](#)
[Recipe 3.3. Passing Local Mail to a Mail Hub](#)
[Recipe 3.4. Passing Apparently Local Mail to a Relay](#)
[Recipe 3.5. Passing UUCP Mail to a Relay](#)
[Recipe 3.6. Relaying Mail for All Hosts in a Domain](#)
[Recipe 3.7. Relaying Mail for Individual Hosts](#)
[Recipe 3.8. Configuring Relaying on a Mail Exchanger](#)
[Recipe 3.9. Loading Class \\$=R via LDAP](#)
[Recipe 3.10. Relaying Only Outbound Mail](#)

[Chapter 4. Masquerading](#)

[Introduction](#)

[Recipe 4.1. Adding Domains to All Sender Addresses](#)
[Recipe 4.2. Masquerading the Sender Hostname](#)
[Recipe 4.3. Eliminating Masquerading for the Local Mailer](#)
[Recipe 4.4. Forcing Masquerading of Local Mail](#)
[Recipe 4.5. Masquerading Recipient Addresses](#)
[Recipe 4.6. Masquerading at the Relay Host](#)
[Recipe 4.7. Limiting Masquerading](#)
[Recipe 4.8. Masquerading All Hosts in a Domain](#)
[Recipe 4.9. Masquerading Most of the Hosts in a Domain](#)
[Recipe 4.10. Masquerading the Envelope Address](#)
[Recipe 4.11. Rewriting the From Address with the genericstable](#)
[Recipe 4.12. Rewriting Sender Addresses for an Entire Domain](#)
[Recipe 4.13. Masquerading with LDAP](#)
[Recipe 4.14. Reading the genericstable via LDAP](#)

[Chapter 5. Routing Mail](#)

[Introduction](#)

[Recipe 5.1. Routing Mail to Special Purpose Mailers](#)
[Recipe 5.2. Sending Error Messages from the mailertable](#)
[Recipe 5.3. Disabling MX Processing to Avoid Loops](#)
[Recipe 5.4. Routing Mail for Local Delivery](#)
[Recipe 5.5. Reading the mailertable via LDAP](#)

[Recipe 5.6. Routing Mail for Individual Virtual Hosts](#)

[Recipe 5.7. Routing Mail for Entire Virtual Domains](#)

[Recipe 5.8. Reading the virtusertable via LDAP](#)

[Recipe 5.9. Routing Mail with LDAP](#)

[Recipe 5.10. Using LDAP Routing with Masquerading](#)

[Chapter 6. Controlling Spam](#)

[Introduction](#)

[Recipe 6.1. Blocking Spam with the access Database](#)

[Recipe 6.2. Preventing Local Users from Replying to Spammers](#)

[Recipe 6.3. Reading the access Database via LDAP](#)

[Recipe 6.4. Using a DNS Blackhole List Service](#)

[Recipe 6.5. Building Your Own DNS Blackhole List](#)

[Recipe 6.6. Whitelisting Blacklisted Sites](#)

[Recipe 6.7. Filtering Local Mail with procmail](#)

[Recipe 6.8. Filtering Outbound Mail with procmail](#)

[Recipe 6.9. Invoking Special Header Processing](#)

[Recipe 6.10. Using Regular Expressions in sendmail](#)

[Recipe 6.11. Identifying Local Problem Users](#)

[Recipe 6.12. Using MILTER](#)

[Recipe 6.13. Bypassing Spam Checks](#)

[Recipe 6.14. Enabling Spam Checks on a Per-User Basis](#)

[Chapter 7. Authenticating with AUTH](#)

[Introduction](#)

[Recipe 7.1. Offering AUTH Authentication](#)

[Recipe 7.2. Authenticating with AUTH](#)

[Recipe 7.3. Storing AUTH Credentials in the authinfo File](#)

[Recipe 7.4. Limiting Advertised Authentication Mechanisms](#)

[Recipe 7.5. Using AUTH to Permit Relaying](#)

[Recipe 7.6. Controlling the AUTH= Parameter](#)

[Recipe 7.7. Avoiding Double Encryption](#)

[Recipe 7.8. Requiring Authentication](#)

[Recipe 7.9. Selectively Requiring Authentication](#)

[Chapter 8. Securing the Mail Transport](#)

[Introduction](#)

[Recipe 8.1. Building a Private Certificate Authority](#)

[Recipe 8.2. Creating a Certificate Request](#)

[Recipe 8.3. Signing a Certificate Request](#)

[Recipe 8.4. Configuring sendmail for STARTTLS](#)

[Recipe 8.5. Relaying Based on the CA](#)

[Recipe 8.6. Relaying Based on the Certificate Subject](#)

[Recipe 8.7. Requiring Outbound Encryption](#)

[Recipe 8.8. Requiring Inbound Encryption](#)

[Recipe 8.9. Requiring a Verified Certificate](#)

[Recipe 8.10. Requiring TLS for a Recipient](#)

[Recipe 8.11. Refusing STARTTLS Service](#)

[Recipe 8.12. Selectively Advertising STARTTLS](#)

[Recipe 8.13. Requesting Client Certificates](#)

[Chapter 9. Managing the Queue](#)

[Introduction](#)

[Recipe 9.1. Creating Multiple Queues](#)

[Recipe 9.2. Using qf, df, and xf Subdirectories](#)

[Recipe 9.3. Defining Queue Groups](#)

[Recipe 9.4. Assigning Recipients to Specific Queues](#)

[Recipe 9.5. Using Persistent Queue Runners](#)

[Recipe 9.6. Using a Queue Server](#)

[Recipe 9.7. Setting Protocol Timers](#)

[Chapter 10. Securing sendmail](#)

[Introduction](#)

[Recipe 10.1. Limiting the Number of sendmail Servers](#)

[Recipe 10.2. Limiting the Number of Network Accessible Servers](#)

[Recipe 10.3. Updating to Close Security Holes](#)

[Recipe 10.4. Patching to Close Security Holes](#)

[Recipe 10.5. Disabling Delivery to Programs](#)

[Recipe 10.6. Controlling Delivery to Programs](#)

[Recipe 10.7. Disabling Delivery to Files](#)

[Recipe 10.8. Bypassing User .forward Files](#)

[Recipe 10.9. Controlling Delivery to Files](#)

[Recipe 10.10. Running sendmail Non-Set-User-ID root](#)

[Recipe 10.11. Setting a Safe Default User ID](#)

[Recipe 10.12. Defining Trusted Users](#)

[Recipe 10.13. Identifying the sendmail Administrator](#)

[Recipe 10.14. Limiting the SMTP Command Set](#)

[Recipe 10.15. Requiring a Valid HELO](#)

[Recipe 10.16. Restricting Command-Line Options](#)

[Recipe 10.17. Denying DoS Attacks](#)

[Colophon](#)

[Index](#)

[\[Team LiB \]](#)