

Contents

About This Addendum	v	Exchanging a PMC Adapter on a Standard System Card	7
Before You Start	v	Exchanging a PMC Adapter on a High-Performance System Card (FRU PN 02L2370)	9
Equipment You Need	v	Exchanging a PMC Adapter on a High-Performance System Card (Not for FRU PN 02L2370)	11
Safety Precautions	v		
Disconnecting the Power Cord	v		
Reconnecting the Power Cord	vi		
Handling Static-Sensitive Devices	vi		
Chapter 1. Installing a PMC Adapter	1	Chapter 3. Notices	13
Installing a PMC Adapter on a Standard System Card	1	Notice to Users of Online Versions of This Book	13
Installing a PMC Adapter on a High-Performance System Card (FRU PN 02L2370)	2	Trademarks	13
Installing a PMC Adapter on a High-Performance System Card (Not for FRU PN 02L2370)	4		
		Chapter 4. Safety Information	15
Chapter 2. Exchanging a PMC Adapter	7	Readers' Comments — We'd Like to Hear from You	25

You need the following equipment to remove and replace features in the IBM 2212:

- Flat-blade screwdriver
- Phillips screwdriver
- Screw starter (optional)

Safety Precautions

DANGER

Before you begin to install this product, read the safety information in *Caution: Safety Information—Read This First, SD21-0030*. This booklet describes safe procedures for cabling and plugging in electrical equipment.

Note: For translations of safety notices, see "Chapter 4. Safety Information" on page 15.

Also read the safety notices in "Chapter 4. Safety Information" on page 15.

Disconnecting the Power Cord