

---

# CONTENTS

---

|                                                     |          |
|-----------------------------------------------------|----------|
| <b>Preface</b>                                      | xxiii    |
| <b>Acknowledgements</b>                             | xxv      |
| <br>                                                |          |
| <b>1. Fundamental Wide Area Networking Concepts</b> | <b>1</b> |
| 1.1 Communications System Components                | 2        |
| 1.2 Line Connections                                | 2        |
| Dedicated line                                      | 2        |
| Leased line                                         | 2        |
| Switched line                                       | 3        |
| Cost trends                                         | 4        |
| Factors to consider                                 | 4        |
| 1.3 Types of Services and Transmission Devices      | 5        |
| Digital repeaters                                   | 6        |
| Unipolar and bipolar signaling                      | 6        |
| Other digital signaling methods                     | 7        |
| Modems                                              | 7        |
| Signal conversion                                   | 7        |
| Acoustic couplers                                   | 8        |
| Signal conversion                                   | 8        |
| Analog facilities                                   | 9        |
| DDD                                                 | 9        |
| WATS                                                | 10       |
| FX                                                  | 11       |
| Leased lines                                        | 13       |
| Digital facilities                                  | 14       |
| Digital signaling                                   | 14       |
| Unipolar non-return to zero                         | 14       |
| Unipolar return to zero                             | 16       |
| Bipolar return to zero                              | 16       |
| Evolution of service offerings                      | 17       |
| AT&T offerings                                      | 18       |
| European offerings                                  | 20       |
| DSUs                                                | 20       |
| 1.4 Transmission Mode                               | 22       |
| Simplex transmission                                | 22       |
| Half-duplex transmission                            | 22       |
| Full-duplex transmission                            | 23       |
| Terminal and mainframe computer operations          | 25       |
| Different character displays                        | 26       |
| 1.5 Transmission Techniques                         | 27       |
| Asynchronous transmission                           | 27       |
| Synchronous transmission                            | 29       |

|      |                                                                 |     |
|------|-----------------------------------------------------------------|-----|
| 1.6  | Types of Transmission                                           | 30  |
| 1.7  | Line Structure                                                  | 31  |
|      | Types of line structure                                         | 31  |
|      | Point-to-point                                                  | 32  |
|      | Multipoint                                                      | 33  |
| 1.8  | Line Discipline                                                 | 33  |
| 1.9  | Network Topology                                                | 35  |
| 1.10 | Transmission Rate                                               | 36  |
|      | Analog service                                                  | 36  |
|      | Digital service                                                 | 37  |
| 1.11 | Transmission Codes                                              | 38  |
|      | Morse code                                                      | 39  |
|      | Baudot code                                                     | 39  |
|      | BCD code                                                        | 41  |
|      | EBCDIC code                                                     | 42  |
|      | ASCII code                                                      | 42  |
|      | Extended ASCII                                                  | 43  |
|      | Code conversion                                                 | 46  |
| 1.12 | Error Detection and Correction                                  | 47  |
|      | Asynchronous transmission                                       | 48  |
|      | Parity checking                                                 | 48  |
|      | Block checking                                                  | 51  |
|      | Synchronous transmission                                        | 53  |
|      | Cyclic codes                                                    | 54  |
| 1.13 | Standards Organizations, Activities and the OSI Reference Model | 58  |
|      | National standards organizations                                | 59  |
|      | ANSI                                                            | 59  |
|      | EIA                                                             | 60  |
|      | FIPS                                                            | 62  |
|      | IEEE                                                            | 62  |
|      | BSI                                                             | 62  |
|      | CSA                                                             | 63  |
|      | International standards organizations                           | 63  |
|      | ITU                                                             | 63  |
|      | ISO                                                             | 64  |
|      | De facto standards                                              | 64  |
|      | AT&T compatibility                                              | 67  |
|      | Cross-licensed technology                                       | 68  |
|      | Bellcore                                                        | 68  |
|      | Internet standards                                              | 69  |
|      | The ISO reference model                                         | 70  |
|      | Layered architecture                                            | 71  |
|      | OSI layers                                                      | 71  |
|      | Data flow                                                       | 74  |
| 1.14 | The Physical Layer: Cables, Connectors, Plugs and Jacks         | 75  |
|      | DTE/DCE interfaces                                              | 76  |
|      | Connector overview                                              | 77  |
|      | RS-232-C/D                                                      | 79  |
|      | RS-232-E                                                        | 89  |
|      | RS-232/V.24 limitations                                         | 89  |
|      | Differential signaling                                          | 90  |
|      | RS-449                                                          | 91  |
|      | V.35                                                            | 93  |
|      | RS-366-A                                                        | 93  |
|      | X.21 and X.20                                                   | 95  |
|      | X.21 bis                                                        | 98  |
|      | RS-530                                                          | 98  |
|      | High Speed Serial Interface                                     | 100 |

|                                           |            |
|-------------------------------------------|------------|
| Rationale for development                 | 100        |
| Signal definitions                        | 101        |
| Loopback circuits                         | 103        |
| Pin assignments                           | 104        |
| Applications                              | 105        |
| High Performance Parallel Interface       | 105        |
| Transmission distance                     | 105        |
| Operation                                 | 106        |
| Cables and connectors                     | 106        |
| Twisted-pair cable                        | 107        |
| Low-capacitance shielded cable            | 107        |
| Ribbon cable                              | 107        |
| The RS-232 null modem                     | 107        |
| RS-232 cabling tricks                     | 110        |
| Plugs and jacks                           | 111        |
| Connecting arrangements                   | 114        |
| Permissive arrangement                    | 114        |
| Fixed loss loop arrangement               | 114        |
| Programmable arrangement                  | 115        |
| Telephone options                         | 115        |
| Ordering the business line                | 117        |
| 1.15 The Data Link Layer                  | 117        |
| Terminal and data link protocols          | 118        |
| Connection establishment and verification | 118        |
| Transmission sequence                     | 119        |
| Error control                             | 119        |
| Types of protocols                        | 120        |
| Teletype protocols                        | 121        |
| XMODEM protocol                           | 126        |
| XMODEM/CRC protocol                       | 128        |
| YMODEM and YMODEM batch protocols         | 129        |
| XMODEM-1K protocol                        | 132        |
| YMODEM-G and YMODEM-G batch protocols     | 132        |
| ZMODEM                                    | 133        |
| Kermit                                    | 134        |
| Bisynchronous protocols                   | 136        |
| DDCMP                                     | 142        |
| Bit-oriented protocols                    | 144        |
| Other protocols                           | 151        |
| 1.16 Integrated Services Digital Network  | 151        |
| Concept behind ISDN                       | 152        |
| ISDN architecture                         | 152        |
| Types of service                          | 153        |
| Basic access                              | 153        |
| Primary access                            | 157        |
| Other channels                            | 157        |
| Network characteristics                   | 158        |
| Terminal equipment and network interfaces | 159        |
| TE1                                       | 159        |
| TE2                                       | 160        |
| Terminal adapters                         | 160        |
| NT1                                       | 162        |
| NT2                                       | 163        |
| Interfaces                                | 163        |
| The future of ISDN                        | 164        |
| <b>Review Questions</b>                   | <b>165</b> |

|                                             |            |
|---------------------------------------------|------------|
| <b>2. Wide Area Networks</b>                | <b>171</b> |
| 2.1 Overview                                | 171        |
| Transmission facilities                     | 172        |
| 2.2 Circuit Switched Networks               | 172        |
| Frequency division multiplexing             | 173        |
| ITU FDM recommendations                     | 174        |
| Time division multiplexing                  | 175        |
| T-carrier evolution                         | 175        |
| Channel banks                               | 176        |
| T1 multiplexer                              | 177        |
| Circuit switching characteristics           | 178        |
| 2.3 Leased Line Based Networks              | 178        |
| Types of leased lines                       | 179        |
| Utilization examples                        | 179        |
| Multiplexer utilization                     | 180        |
| Router utilization                          | 182        |
| 2.4 Packet Switching Networks               | 183        |
| Multiplexing as opposed to packet switching | 183        |
| Packet network construction                 | 184        |
| ITU packet network recommendations          | 184        |
| The PDN and value-added networks            | 185        |
| Packet network architecture                 | 186        |
| Datagram packet networks                    | 186        |
| Virtual circuit packet networks             | 187        |
| Packet formation                            | 187        |
| X.25                                        | 188        |
| Packet format and content                   | 188        |
| Call establishment                          | 190        |
| Flow control                                | 191        |
| Advantages of PDNs                          | 191        |
| Technological advances                      | 191        |
| Packet network delay problems               | 192        |
| Fast packet switching                       | 193        |
| Frame relay                                 | 194        |
| Comparison to X.25                          | 194        |
| Utilization                                 | 195        |
| Operation                                   | 196        |
| Cost                                        | 199        |
| Voice over frame relay                      | 200        |
| 2.5 The Internet                            | 201        |
| TCP/IP                                      | 202        |
| Protocol development                        | 202        |
| The TCP/IP structure                        | 202        |
| Datagrams versus virtual circuits           | 205        |
| ICMP and ARP                                | 208        |
| The TCP header                              | 208        |
| Source and destination port fields          | 209        |
| Sequence field                              | 210        |
| Control field flags                         | 210        |
| Window field                                | 211        |
| Checksum field                              | 211        |
| Urgent pointer field                        | 211        |
| TCP transmission sequence example           | 211        |
| The UDP header                              | 213        |
| Source and destination port fields          | 214        |
| Length field                                | 214        |
| The IP header                               | 214        |

|                                           |     |
|-------------------------------------------|-----|
| Version field                             | 214 |
| Header length and total length fields     | 215 |
| Type of service field                     | 215 |
| Identification and fragment offset fields | 217 |
| Time to live field                        | 217 |
| Flags field                               | 217 |
| Protocol field                            | 217 |
| Source and destination address fields     | 217 |
| IP addressing                             | 218 |
| Class A                                   | 219 |
| Class B                                   | 219 |
| Class C                                   | 219 |
| Host restrictions                         | 219 |
| Subnetting                                | 219 |
| Subnet masks                              | 220 |
| Domain Name Service                       | 221 |
| Name server                               | 223 |
| TCP/IP configuration                      | 224 |
| IPv6                                      | 226 |
| Evolution                                 | 226 |
| Overview                                  | 227 |
| Addressing                                | 229 |
| Migration issues                          | 233 |
| 2.6 SNA and APPN                          | 235 |
| SNA concepts                              | 235 |
| SSCP                                      | 236 |
| Network nodes                             | 236 |
| The physical unit                         | 236 |
| The logical unit                          | 237 |
| Multiple session capability               | 237 |
| SNA network structure                     | 237 |
| Types of physical units                   | 239 |
| Multiple domains                          | 239 |
| SNA layers                                | 241 |
| Physical and data link layers             | 241 |
| Path control layer                        | 241 |
| Transmission control layer                | 242 |
| Data flow control services                | 242 |
| Presentation services layer               | 242 |
| Transaction service layer                 | 243 |
| SNA developments                          | 243 |
| SNA sessions                              | 244 |
| LU-to-LU sessions                         | 244 |
| Addressing                                | 244 |
| Advanced Peer-to-Peer Networking (APPN)   | 246 |
| APPC concepts                             | 246 |
| APPN architecture                         | 247 |
| Operation                                 | 248 |
| Route selection                           | 250 |
| 2.7 ATM                                   | 251 |
| Overview                                  | 251 |
| Cell size                                 | 252 |
| Benefits                                  | 252 |
| The ATM protocol stack                    | 255 |
| ATM Adaptation Layer (AAL)                | 255 |
| The ATM Layer                             | 256 |
| The Physical Layer                        | 257 |
| ATM operation                             | 257 |
| Components                                | 258 |
| Network interfaces                        | 258 |

|                                                                  |            |
|------------------------------------------------------------------|------------|
| The ATM cell header                                              | 259        |
| ATM connections and cell switching                               | 262        |
| <b>Review Questions</b>                                          | <b>264</b> |
| <b>3. Local Area Networks</b>                                    | <b>269</b> |
| 3.1 Overview                                                     | 269        |
| Origin                                                           | 270        |
| Comparison to WANs                                               | 270        |
| Geographic area                                                  | 270        |
| Data transmission and error rates                                | 271        |
| Ownership                                                        | 271        |
| Regulation                                                       | 271        |
| Data routing and topology                                        | 272        |
| Type of information carried                                      | 272        |
| Utilization benefits                                             | 273        |
| Peripheral sharing                                               | 273        |
| Common software access                                           | 273        |
| Electronic mail                                                  | 273        |
| Gateway access to mainframes                                     | 273        |
| 3.2 Technological Characteristics                                | 274        |
| Topology                                                         | 274        |
| Loop                                                             | 274        |
| Bus                                                              | 275        |
| Ring                                                             | 275        |
| Star                                                             | 275        |
| Tree                                                             | 275        |
| Mixed topologies                                                 | 276        |
| Comparison of topologies                                         | 276        |
| Signaling methods                                                | 277        |
| Broadband versus baseband                                        | 277        |
| Broadband signaling                                              | 277        |
| Baseband signaling                                               | 278        |
| Transmission medium                                              | 279        |
| Twisted-pair                                                     | 280        |
| Coaxial cable                                                    | 288        |
| Fiber optic cable                                                | 291        |
| Access method                                                    | 292        |
| Listeners and talkers                                            | 292        |
| Carrier-Sense Multiple Access with Collision Detection (CSMA/CD) | 293        |
| Token passing                                                    | 294        |
| 3.3 IEEE 802 Standards                                           | 296        |
| 802 committees                                                   | 297        |
| Data link subdivision                                            | 298        |
| Medium Access Control                                            | 299        |
| Logical Link Control                                             | 299        |
| Physical layer subdivision                                       | 300        |
| 3.4 Ethernet Networks                                            | 300        |
| Original network components                                      | 300        |
| Coaxial cable                                                    | 300        |
| Transceiver and transceiver cable                                | 301        |
| Interface board                                                  | 302        |
| Repeaters                                                        | 302        |
| IEEE 802.3 networks                                              | 303        |
| Network names                                                    | 303        |
| 10BASE-5                                                         | 303        |
| 10BASE-2                                                         | 305        |
| 10BROAD-36                                                       | 306        |

|                                                    |            |
|----------------------------------------------------|------------|
| 1BASE-5                                            | 307        |
| 10BASE-T                                           | 308        |
| 100BASE-T                                          | 311        |
| 100BASE-T4                                         | 313        |
| 100BASE-TX                                         | 315        |
| 100BASE-FX                                         | 317        |
| Network utilization                                | 317        |
| Gigabit Ethernet                                   | 319        |
| Frame composition                                  | 320        |
| Preamble field                                     | 321        |
| Start of frame delimiter field                     | 321        |
| Destination address field                          | 321        |
| Source address field                               | 323        |
| Type field                                         | 324        |
| Length field                                       | 324        |
| Data field                                         | 324        |
| Frame check sequence field                         | 324        |
| Media Access Control (MAC) overview                | 325        |
| Logical Link Control (LLC) overview                | 325        |
| Types and classes of service                       | 326        |
| Type 1                                             | 326        |
| Type 2                                             | 327        |
| Type 3                                             | 327        |
| Classes of service                                 | 328        |
| 3.5 Token-Ring                                     | 328        |
| Redundant versus non-redundant main ring paths     | 329        |
| Cabling and device restrictions                    | 329        |
| Intra-MAU cabling distances                        | 330        |
| Adjusted ring length                               | 332        |
| Other ring size considerations                     | 332        |
| Transmission formats                               | 334        |
| Token                                              | 334        |
| Abort                                              | 334        |
| Frame                                              | 334        |
| Starting/ending delimiters                         | 335        |
| Access control                                     | 337        |
| Frame control                                      | 338        |
| Destination address                                | 339        |
| Source address                                     | 340        |
| Routing information                                | 341        |
| Information field                                  | 342        |
| Frame check sequence                               | 342        |
| Frame status                                       | 342        |
| Medium Access Control                              | 343        |
| MAC control                                        | 343        |
| Purge frame                                        | 344        |
| Beacon frame                                       | 344        |
| Duplicate address test frame                       | 345        |
| Logical Link Control                               | 345        |
| <b>Review Questions</b>                            | <b>346</b> |
| <b>4. Wide Area Network Transmission Equipment</b> | <b>351</b> |
| 4.1 Acoustic Couplers                              | 351        |
| US and European compatibility                      | 352        |
| Operation                                          | 354        |
| Problems in usage                                  | 354        |
| 4.2 Modems                                         | 355        |

|                                      |     |
|--------------------------------------|-----|
| Basic components                     | 356 |
| Modem transmitter section            | 356 |
| Scramblers                           | 358 |
| Modulator, amplifier and filter      | 358 |
| Equalizer                            | 359 |
| Bandwidth                            | 359 |
| Delay distortion                     | 361 |
| The modulation process               | 363 |
| Amplitude modulation                 | 363 |
| Frequency modulation                 | 364 |
| Phase modulation                     | 365 |
| Bps versus baud                      | 366 |
| Voice circuit parameters             | 366 |
| Combined modulation techniques       | 367 |
| Other modulation techniques          | 369 |
| Trellis coded modulation             | 370 |
| Convolutional encoder operation      | 371 |
| Echo cancellation                    | 372 |
| Types of modems and features         | 373 |
| Mode of transmission                 | 373 |
| Transmission technique               | 373 |
| Line use classification              | 374 |
| Intelligence                         | 375 |
| Method of fabrication                | 375 |
| Reverse and secondary channels       | 376 |
| Equalization                         | 377 |
| Synchronization                      | 378 |
| Multiport capability                 | 378 |
| Security capability                  | 379 |
| Multiple speed selection capability  | 379 |
| Voice/data capability                | 380 |
| Modem operations and compatibility   | 380 |
| 300 bps                              | 380 |
| Echo suppression                     | 382 |
| Disabling echo suppressors           | 383 |
| 300 to 1800 bps                      | 383 |
| 2400 bps                             | 388 |
| 4800 bps                             | 391 |
| 9600 bps                             | 393 |
| 14 400 bps                           | 399 |
| 19 200 bps                           | 405 |
| 28 800 bps                           | 409 |
| 33 600 bps                           | 415 |
| 56 kbps                              | 415 |
| Non-standard modems                  | 418 |
| Packetized ensemble protocol         | 418 |
| Asymmetrical modems                  | 419 |
| Ping-pong modems                     | 421 |
| Modem handshaking                    | 421 |
| Modem testing and problem resolution | 422 |
| Using modem indicators               | 423 |
| Modem testing                        | 427 |
| 4.3 Intelligent Modems               | 431 |
| Command sets                         | 431 |
| The Hayes command set                | 432 |
| Command use                          | 433 |
| Result codes                         | 434 |
| Extended AT commands                 | 435 |
| Modem registers                      | 437 |
| Compatibility                        | 438 |



|                                           |     |
|-------------------------------------------|-----|
| Error detection and correction            | 439 |
| Flow control                              | 439 |
| Methods of error detection and correction | 442 |
| Rationale                                 | 443 |
| MNP                                       | 444 |
| LAP-M                                     | 453 |
| Compatibility issues                      | 453 |
| Data compression                          | 454 |
| Rationale                                 | 454 |
| MNP Class 5 compression                   | 454 |
| MNP Class 7 enhanced data compression     | 457 |
| V.42 bis                                  | 459 |
| Compatibility issues                      | 461 |
| Throughput issues                         | 461 |
| Negotiation problems                      | 462 |
| Simultaneous voice and data operations    | 463 |
| Synchronous dialing language              | 465 |
| 4.4 Multiport Modems                      | 466 |
| Operation                                 | 466 |
| Selection criteria                        | 467 |
| Application example                       | 467 |
| Standard and optional features            | 470 |
| 4.5 Multipoint Modems                     | 472 |
| Factors affecting multipoint circuits     | 473 |
| Response time                             | 473 |
| Transaction rate                          | 473 |
| Delay factors                             | 473 |
| Throughput problems                       | 475 |
| Multipoint modem developments             | 476 |
| Remote multipoint testing                 | 477 |
| 4.6 Security Modems                       | 477 |
| Operation                                 | 477 |
| Memory capacity and device access         | 478 |
| Device limitations                        | 478 |
| 4.7 Line Drivers                          | 479 |
| Direct connection                         | 480 |
| Using line drivers                        | 482 |
| Applications                              | 483 |
| 4.8 Limited-distance Modems               | 484 |
| Rationale and status                      | 485 |
| Contrasting devices                       | 485 |
| Transmission media                        | 485 |
| Operational features                      | 487 |
| Diagnostics                               | 488 |
| 4.9 Broadband Modems                      | 489 |
| Telephone and cable TV infrastructure     | 489 |
| Telephone                                 | 490 |
| Cable TV                                  | 491 |
| Cable modems                              | 494 |
| LANcity LCP                               | 494 |
| IEEE 802.14 proposal                      | 497 |
| DSL modems                                | 499 |
| 4.10 Digital Service Units                | 505 |
| Comparison of facilities                  | 505 |
| Digital signaling                         | 506 |
| Bipolar violations                        | 506 |
| DDS structure                             | 507 |

|                                       |            |
|---------------------------------------|------------|
| Framing formats                       | 508        |
| Signaling structure                   | 510        |
| Timing                                | 511        |
| Service units                         | 511        |
| DSU/CSU tests and indicators          | 513        |
| DDS II                                | 514        |
| Analog extensions to DDS              | 514        |
| Applications                          | 515        |
| KiloStream service                    | 516        |
| The KiloStream network                | 517        |
| 4.11 Channel Service Units            | 518        |
| Comparison to DSU/CSU                 | 520        |
| North American framing                | 520        |
| D4 framing                            | 520        |
| Extended superframe format            | 522        |
| CEPT PCM-30 format                    | 525        |
| Frame composition                     | 525        |
| T-carrier signal characteristics      | 526        |
| North America                         | 527        |
| Europe                                | 529        |
| 4.12 Parallel Interface Extenders     | 529        |
| Extender operation                    | 531        |
| Extender components                   | 532        |
| Application examples                  | 532        |
| <b>Review Question</b>                | <b>533</b> |
| <b>5. LAN Internetworking Devices</b> | <b>539</b> |
| 5.1 Bridges                           | 539        |
| Basic operation                       | 540        |
| Flooding                              | 541        |
| Filtering and forwarding              | 542        |
| Types of bridges                      | 542        |
| Transparent bridge                    | 543        |
| Translating bridge                    | 543        |
| Features                              | 544        |
| Filtering and forwarding              | 545        |
| Selective forwarding                  | 545        |
| Multiple port support                 | 546        |
| Local and wide area interface support | 547        |
| Transparent operation                 | 547        |
| Frame translation                     | 547        |
| Frame encapsulation                   | 547        |
| Fabrication                           | 549        |
| Routing methods                       | 549        |
| Spanning tree protocol                | 550        |
| Source routing                        | 556        |
| Source routing transparent bridges    | 559        |
| Network utilization                   | 560        |
| 5.2 Routers                           | 562        |
| Comparison to bridges                 | 563        |
| Network layer operations              | 564        |
| Network address utilization           | 564        |
| Table operation                       | 565        |
| Advantages of use                     | 565        |
| IP support overview                   | 567        |
| ARP                                   | 569        |
| Communications and routing protocols  | 569        |

|                                                          |            |
|----------------------------------------------------------|------------|
| Routing protocols                                        | 569        |
| Handling non-routable protocols                          | 570        |
| Communications protocols                                 | 570        |
| Protocol-dependent routers                               | 571        |
| Protocol-independent routers                             | 572        |
| Types of routing protocols                               | 575        |
| 5.3 Gateways                                             | 581        |
| Overview                                                 | 581        |
| Mainframe access                                         | 582        |
| Control unit connectivity                                | 582        |
| Ethernet connectivity                                    | 584        |
| Alternative gateway methods                              | 585        |
| 5.4 LAN Switches                                         | 599        |
| Conventional hub bottlenecks                             | 599        |
| Ethernet hub operation                                   | 600        |
| Token-Ring hub operation                                 | 601        |
| Bottleneck creation                                      | 601        |
| Switching operations                                     | 602        |
| Basic components                                         | 603        |
| Key advantages of use                                    | 604        |
| Delay times                                              | 604        |
| Switching techniques                                     | 605        |
| Cross-point switching                                    | 605        |
| Store-and-forward                                        | 606        |
| Hybrid                                                   | 608        |
| Port-based switching                                     | 608        |
| Segment-based switching                                  | 609        |
| Using LAN switches                                       | 611        |
| Network redistribution                                   | 611        |
| Server segmentation                                      | 612        |
| Backbone operation                                       | 612        |
| Handling speed incompatibilities                         | 614        |
| ATM considerations                                       | 615        |
| 5.5 Access Servers                                       | 618        |
| Overview                                                 | 618        |
| Utilization                                              | 619        |
| <b>Review Questions</b>                                  | <b>620</b> |
| <b>6. Wide Area Network Data Concentration Equipment</b> | <b>625</b> |
| Equipment sizing                                         | 625        |
| 6.1 Multiplexers                                         | 626        |
| Evolution                                                | 626        |
| Comparison with other devices                            | 627        |
| Device support                                           | 627        |
| Multiplexing techniques                                  | 627        |
| Frequency division multiplexing                          | 628        |
| Time division multiplexing                               | 634        |
| Multiplexing economics                                   | 640        |
| Statistical and intelligent multiplexers                 | 642        |
| Statistical frame construction                           | 643        |
| Flow control                                             | 645        |
| Service ratio                                            | 646        |
| Data source support                                      | 647        |
| Switching and port contention                            | 647        |
| ITDMs                                                    | 648        |
| STDM/ITDM statistics                                     | 649        |
| Features to consider                                     | 650        |
| Utilization considerations                               | 651        |

|     |                                            |     |
|-----|--------------------------------------------|-----|
| 6.2 | T1/E1 Multiplexers                         | 651 |
|     | The T-carrier                              | 652 |
|     | PCM                                        | 652 |
|     | Sampling                                   | 652 |
|     | Quantization                               | 653 |
|     | Coding                                     | 654 |
|     | DS1 framing                                | 654 |
|     | Digital signal levels                      | 655 |
|     | Framing changes                            | 656 |
|     | T1 signal characteristics                  | 657 |
|     | European E1 facilities                     | 657 |
|     | The T1 multiplexer                         | 658 |
|     | Voice digitization techniques              | 659 |
|     | Waveform coding                            | 659 |
|     | Vocoding                                   | 661 |
|     | Linear predictive coding                   | 661 |
|     | Hybrid coding                              | 663 |
|     | CELP coding                                | 663 |
|     | T1 multiplexer employment                  | 664 |
|     | Features to consider                       | 665 |
|     | Bandwidth utilization                      | 666 |
|     | Bandwidth allocation                       | 667 |
|     | Voice interface support                    | 669 |
|     | Voice digitization support                 | 670 |
|     | Internodal trunk support                   | 671 |
|     | Subrate channel utilization                | 671 |
|     | Digital access cross-connect capability    | 673 |
|     | Gateway operation support                  | 673 |
|     | Alternate routing and route generation     | 674 |
|     | Redundancy                                 | 675 |
|     | Maximum number of hops and nodes supported | 676 |
|     | Diagnostics                                | 676 |
|     | Configuration rules                        | 676 |
| 6.3 | Subrate Voice/Data Multiplexers            | 677 |
|     | Operation                                  | 677 |
|     | Utilization                                | 678 |
| 6.4 | Inverse Multiplexers                       | 679 |
|     | Operation                                  | 679 |
|     | Typical applications                       | 680 |
|     | Contingency operations                     | 682 |
|     | Economics of use                           | 683 |
|     | Extended subchannel support                | 683 |
|     | Bandwidth-on-demand                        | 685 |
| 6.5 | Packet Assembler/Disassembler              | 686 |
|     | Applications                               | 687 |
|     | Types of PADs                              | 687 |
|     | X.3 parameters                             | 688 |
| 6.6 | Frame Relay Access Device                  | 692 |
|     | Hardware overview                          | 692 |
|     | Comparison to routers                      | 693 |
|     | The I-FRAD                                 | 693 |
|     | Protocol support                           | 694 |
|     | SNA/SDLC encapsulation into TCP/IP         | 694 |
|     | SNA/SDLC conversion to SNA/LLC2            | 694 |
|     | Data Link Switching                        | 695 |
|     | RFC 1490                                   | 695 |
|     | Voice over Frame Relay                     | 696 |
|     | Fragmentation                              | 696 |
|     | Prioritization                             | 696 |

|                                       |            |
|---------------------------------------|------------|
| Buffering                             | 696        |
| Voice digitization                    | 697        |
| 6.7 Front-end Processors              | 697        |
| Communications controllers            | 699        |
| IBM 3725                              | 700        |
| IBM 3745                              | 702        |
| IBM 3746                              | 705        |
| 6.8 Modem- and Line-sharing Units     | 706        |
| A similar device                      | 707        |
| Operation                             | 707        |
| Device differences                    | 708        |
| Sharing unit constraints              | 709        |
| Other sharing devices                 | 710        |
| 6.9 Port-sharing Units                | 711        |
| When to consider                      | 711        |
| Operation and usage                   | 713        |
| Port-sharing as a supplement          | 715        |
| A similar device                      | 715        |
| 6.10 Control Units                    | 716        |
| Control unit concept                  | 716        |
| Attachment methods                    | 717        |
| Unit operation                        | 718        |
| Protocol support                      | 719        |
| Breaking the closed system            | 720        |
| Protocol converters                   | 720        |
| Terminal interface unit               | 721        |
| 6.11 Port Selectors                   | 722        |
| Types of devices                      | 722        |
| Operation                             | 723        |
| Computer site operations              | 723        |
| Usage decisions                       | 724        |
| Port costs                            | 727        |
| Load balancing                        | 728        |
| Selector features                     | 728        |
| Line-switching network                | 729        |
| 6.12 Protocol Converters              | 730        |
| Operation                             | 731        |
| Physical/electrical conversion        | 731        |
| Data code/speed conversion            | 731        |
| Conversion categories                 | 731        |
| Device operation conversion           | 732        |
| Device functionality conversion       | 732        |
| Character versus block mode operation | 733        |
| Applications                          | 734        |
| <b>Review Questions</b>               | <b>735</b> |
| <b>7. Specialized Devices</b>         | <b>741</b> |
| 7.1 Data Communications Switches      | 741        |
| Fallback switches                     | 742        |
| Bypass switches                       | 743        |
| Crossover switch                      | 744        |
| Matrix switch                         | 744        |
| Additional derivations                | 746        |
| Chaining switches                     | 747        |
| Switch control                        | 748        |

|                                         |     |
|-----------------------------------------|-----|
| Switching applications                  | 750 |
| Hot-start configuration                 | 751 |
| Cold-start configuration                | 752 |
| Sharing a backup router                 | 753 |
| Router to router communications         | 753 |
| Adding a third EIA fallback switch      | 754 |
| Adding more switchable lines            | 755 |
| Chaining adds options                   | 755 |
| Access to other lines                   | 756 |
| 7.2 Data Compression Performing Devices | 757 |
| Compression techniques                  | 757 |
| Character oriented                      | 758 |
| Null compression                        | 758 |
| Run length compression                  | 758 |
| Pattern substitution                    | 759 |
| Statistical encoding                    | 759 |
| Huffman coding                          | 760 |
| LZW coding                              | 761 |
| Benefits of compression                 | 763 |
| Using compression performing devices    | 764 |
| Compression DSUs                        | 764 |
| Multifunctional compression             | 765 |
| 7.3 Fiber Optic Transmission Systems    | 766 |
| System components                       | 767 |
| The light source                        | 767 |
| Optical cables                          | 768 |
| Types of fibers                         | 769 |
| Common cable types                      | 770 |
| The light detector                      | 770 |
| Other optical devices                   | 771 |
| Optical modem                           | 771 |
| Optical multiplexer                     | 772 |
| Transmission advantages                 | 772 |
| Bandwidth                               | 773 |
| Electromagnetic non-susceptibility      | 773 |
| Signal attenuation                      | 774 |
| Electrical hazard                       | 774 |
| Security                                | 774 |
| Weight and size                         | 774 |
| Durability                              | 775 |
| Limitations of use                      | 775 |
| Cable splicing                          | 775 |
| System cost                             | 775 |
| Utilization economics                   | 776 |
| Dedicated cable system                  | 777 |
| Multichannel cable                      | 777 |
| Optical multiplexers                    | 777 |
| 7.4 Security Devices                    | 778 |
| Password shortcomings                   | 779 |
| Password combinations                   | 781 |
| Illicit access                          | 782 |
| Transmission security                   | 784 |
| Manual techniques                       | 785 |
| Automated techniques                    | 787 |
| Modern developments                     | 789 |
| DES algorithm                           | 789 |
| Public versus private keys              | 790 |
| On-line applications                    | 791 |
| LAN security                            | 794 |
| Routers                                 | 794 |

|                                                               |            |
|---------------------------------------------------------------|------------|
| Access lists                                                  | 794        |
| Configuring an access list                                    | 795        |
| Extended access lists                                         | 797        |
| Additional extensions                                         | 798        |
| Router access                                                 | 799        |
| Threats not handled                                           | 799        |
| Firewalls                                                     | 799        |
| Placement                                                     | 800        |
| Features                                                      | 801        |
| Proxy services                                                | 802        |
| Using classes                                                 | 803        |
| Address translation                                           | 803        |
| Stateful inspection                                           | 804        |
| Alerts                                                        | 805        |
| Authentication                                                | 806        |
| Packet filtering                                              | 808        |
| The gap to consider                                           | 810        |
| <b>Review Questions</b>                                       | <b>811</b> |
| <b>Appendix A. Sizing Data Communications Network Devices</b> | <b>813</b> |
| A.1 Device Sizing                                             | 813        |
| Sizing problem similarities                                   | 814        |
| Telephone terminology relationships                           | 815        |
| The decision model                                            | 817        |
| Traffic measurements                                          | 818        |
| Erlangs and call-seconds                                      | 819        |
| Grade of service                                              | 820        |
| Route dimensioning parameters                                 | 820        |
| Traffic dimensioning formula                                  | 821        |
| A.2 The Erlang Traffic Formula                                | 821        |
| Multiplexer sizing                                            | 823        |
| A.3 The Poisson Formula                                       | 826        |
| Multiplexer sizing                                            | 826        |
| Formula comparison                                            | 828        |
| Economic constraints                                          | 829        |
| A.4 Applying the Equipment Sizing Process                     | 829        |
| <b>Appendix B. Erlang Distribution Program</b>                | <b>833</b> |
| <b>Appendix C. Poisson Distribution Program</b>               | <b>835</b> |
| <b>Appendix D. Multidrop Line Routing Analysis</b>            | <b>837</b> |
| The minimum-spanning-tree technique                           | 837        |
| The minimum-spanning-tree algorithm                           | 839        |
| Minimum-spanning-tree problems                                | 840        |
| Terminal response times                                       | 840        |
| Probability of transmission errors                            | 841        |
| Front-end processor limitations                               | 842        |
| Large network design                                          | 842        |
| <b>Appendix E. CSMA/CD Network Performance</b>                | <b>843</b> |
| Determining the network frame rate                            | 843        |
| <b>Index</b>                                                  | <b>847</b> |